

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

1 Identification

- **Product Identifier**
- **Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods**
- **Product Number:**
 - Specification: A5.22
 - Classification: E2209T1-1/4, E2594T1-1/4, E307T1-1/4, E308HT1-1/4, E308LT0-1/4, E308LT1-1/4, E309LMoT1-1/4, E309LT0-1/4, E309LT1-1/4, E309T1-1/4, E310T1-1/4, E316HT1-1/4, E316LT0-1/4, E316LT1-1/4, E317LT1-1/4, E347T1-1/4, E410NiMoT1-1/4, E410T1-1/4, EC2209, EC308LSi, EC309L, EC309LSi, EC316LSi, EC410
 - Stainless steel flux cored and metal cored welding electrodes and rods
- **Relevant identified uses of the substance or mixture and uses advised against:**
 - For professional use only. Use according to manufacturer's specification.
- **Product Description:** Stainless steel flux cored and metal cored welding electrodes and rods.
- **Application of the substance / the mixture:** Industry specific application.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
 - Pinnacle Alloys I, LLC
 - 9384 Wallisville Road
 - Houston, TX 77013
 - Telephone: 800-856-9353
- **Emergency telephone number:** 713-688-9353

2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Health hazard

Carcinogenicity 1A

H350 May cause cancer. Route of exposure: Inhalation.

Specific Target Organ Toxicity - Repeated Exposure 1

H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.



Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Eye Irritation 2B

H320 Causes eye irritation.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger
- **Hazard-determining components of labeling:**
 - Nickel
 - Titanium Dioxide
 - Titanium

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

Silica

· Hazard statements:

H320 Causes eye irritation.

H317 May cause an allergic skin reaction.

H350 May cause cancer. Route of exposure: Inhalation.

H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

· Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

43.1 % of the mixture consists of component(s) of unknown toxicity.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· NFPA ratings (scale 0 - 4)



Health = 1

Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1

Fire = 0

Physical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

· Non-hazardous components:

CAS: 7439-89-6	Iron	Balance%
RTECS: NO 4565500		

· Chemical characterization: Substance

· Description: Mixture of substances listed below with non-hazardous additions.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

· Dangerous Components:		
CAS: 7440-47-3 RTECS: GB 4200000	Chromium	0-30%
CAS: 7440-02-0	Nickel	0-25%
	⚠ Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 1, H372; ⚠ Sensitization - Skin 1, H317; Aquatic Acute 3, H402	
CAS: 13463-67-7	Titanium Dioxide	0-15%
	⚠ Carcinogenicity 2, H351	
CAS: 7440-32-6 RTECS: XR 1700000	Titanium	0-11%
	⚠ Skin Irritation 2, H315; Sensitization - Skin 1, H317; Eye Irritation 2B, H320	
CAS: 7439-96-5 RTECS: OO 9275000	Manganese	0-5%
	⚠ Pyrophoric Solids 1, H250; Substances and mixtures which, in contact with water, emit flammable gases 1, H260	
CAS: 7440-67-7 RTECS: ZH 7070000	Zirconium	0-5%
	⚠ Pyrophoric Solids 1, H250; Substances and mixtures which, in contact with water, emit flammable gases 1, H260	
CAS: 7439-98-7 RTECS: QA 4680000	Molybdenum	0-4.5%
CAS: 1344-28-1 RTECS: BD 1200000	Aluminum Oxide	0-3%
	⚠ Specific Target Organ Toxicity - Single Exposure 3, H335	
CAS: 7631-86-9	Silicon Dioxide	0-6%
	⚠ Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335; Eye Irritation 2B, H320	
CAS: 7440-21-3	Silicon	0-2.5%
	⚠ Flammable Solids 2, H228; ⚠ Acute Toxicity - Oral 4, H302; Eye Irritation 2B, H320; Combustible Dust	
CAS: 1314-23-4 RTECS: ZH8800000	Zirconium oxide	0-2%
CAS: 1317-95-9	Silica	0-2%
	⚠ Carcinogenicity 1A, H350; ⚠ Specific Target Organ Toxicity - Single Exposure 3, H335	
CAS: 7429-90-5 RTECS: BD 0330000	Aluminium	0-1%
	⚠ Flammable Solids 2, H228	

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

Note: Certain chemical constituents listed in Section 3 may vary depending upon the Classification of the Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods products.

* 4 First-Aid Measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in the side position for transportation.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: **Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods**

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

- **After eye contact:**

Do NOT rub eyes. Immediately rinse opened eye(s) for at least 15 minutes under running water, lifting upper and lower lids occasionally. If symptoms persist, consult a physician.

If easy to do so, remove contact lenses if worn.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting without medical advice.

- **Information for doctor**

- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

5 Fire-Fighting Measures

- **Extinguishing media**

- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

- **For safety reasons unsuitable extinguishing agents:** No further relevant information.

- **Special hazards arising from the substance or mixture:**

Amorphous or crystalline silicon both react exothermically when heated with alkali-metal carbonates attaining incandescence and evolving carbon monoxide.

Material in powder form, capable of creating a dust explosion. Mixture of silicon, aluminum, and lead oxide explodes when heated.

Moderate fire hazard when it is in the form of a dust (powder) and burns rapidly when heated in flame.

Chromium is attacked vigorously by fused potassium chlorate producing vivid incandescence. Pyrophoric chromium unites with nitric oxide with incandescence. Incandescent reaction with nitrogen oxide or sulfur dioxide.

Special Remarks on Explosion Hazards:

Powdered Chromium metal +fused ammonium nitrate may react violently or explosively. Powdered Chromium will explode spontaneously in air.

Material in powder form is capable of creating a dust explosion. Mixture of silicon, aluminum, and lead oxide explodes when heated.

Amorphous or crystalline silicon both react exothermically when heated with alkali-metal carbonates attaining incandescence and evolving carbon monoxide. Mixtures of silicon, aluminum, and lead explode when heated.

If incinerated, product will release the following toxic fumes: Oxides of iron, carbon, chromium, nickel, molybdenum, manganese, silicon, titanium, aluminum, zirconium, and fluorides and ozone.

- **Advice for firefighters**

- **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

- **Additional information:**

At temperatures above 200°C Zirconium reacts exothermically with the following: fluorine, chloride, bromide, iodine, halocarbons, carbon tetrachloride, carbon, tetra fluoride and Freon's.

These items are not reactive, flammable, or explosive and essentially not hazardous at ambient temperatures.

Welding arcs and sparks can ignite combustibles and flammable products. If involved in a fire, these products may generate irritating aluminum fumes and a variety of metal oxides. Emergency responders must wear personal protection equipment suitable for the situation. Use the extinguishing media recommended for the burning materials and fire situation. See ANSI Z49.1 "Safety in Welding and Cutting" and "Safe Practices" Code: SP, published by the American Welding Society.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures:**

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

· **Environmental precautions:** Do not allow product to reach sewage system or any water system.

· **Methods and material for containment and cleaning up:**

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Flammable solid. Stop leak if without risk. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources.

· **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **PAC-1:**

7439-89-6	Iron	3.2 mg/m ³
7440-47-3	Chromium	1.5 mg/m ³
7440-02-0	Nickel	4.5 mg/m ³
13463-67-7	Titanium Dioxide	30 mg/m ³
7440-32-6	Titanium	30 mg/m ³
7439-96-5	Manganese	3 mg/m ³
7440-67-7	Zirconium	10 mg/m ³
7439-98-7	Molybdenum	30 mg/m ³
1344-28-1	Aluminum Oxide	15 mg/m ³
7631-86-9	Silicon Dioxide	18 mg/m ³
7440-21-3	Silicon	45 mg/m ³
1314-23-4	Zirconium oxide	14 mg/m ³
7440-44-0	Carbon Fiber	6 mg/m ³

· **PAC-2:**

7439-89-6	Iron	35 mg/m ³
7440-47-3	Chromium	17 mg/m ³
7440-02-0	Nickel	50 mg/m ³
13463-67-7	Titanium Dioxide	330 mg/m ³
7440-32-6	Titanium	330 mg/m ³
7439-96-5	Manganese	5 mg/m ³
7440-67-7	Zirconium	83 mg/m ³
7439-98-7	Molybdenum	330 mg/m ³
1344-28-1	Aluminum Oxide	170 mg/m ³
7631-86-9	Silicon Dioxide	740 mg/m ³
7440-21-3	Silicon	100 mg/m ³
1314-23-4	Zirconium oxide	110 mg/m ³
7440-44-0	Carbon Fiber	330 mg/m ³

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

· PAC-3:		
7439-89-6	Iron	150 mg/m ³
7440-47-3	Chromium	99 mg/m ³
7440-02-0	Nickel	99 mg/m ³
13463-67-7	Titanium Dioxide	2,000 mg/m ³
7440-32-6	Titanium	2,000 mg/m ³
7439-96-5	Manganese	1,800 mg/m ³
7440-67-7	Zirconium	500 mg/m ³
7439-98-7	Molybdenum	2,000 mg/m ³
1344-28-1	Aluminum Oxide	990 mg/m ³
7631-86-9	Silicon Dioxide	4,500 mg/m ³
7440-21-3	Silicon	630 mg/m ³
1314-23-4	Zirconium oxide	680 mg/m ³
7440-44-0	Carbon Fiber	2,000 mg/m ³

7 Handling and Storage

· Handling

· Precautions for safe handling:

Avoid creating and breathing dust/fume/gas/mist/vapors/spray.

Ensure good ventilation/exhaustion at the workplace.

· Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

Store away from strong acids, strong bases, strong oxidizing agents and strong reducing agents.

· Storage

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s): No further relevant information available.

* 8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· Components with occupational exposure limits:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituents have no known exposure limits.

7440-47-3 Chromium

PEL	Long-term value: 1 mg/m ³
REL	Long-term value: 0.5* mg/m ³ *metal+inorg.compds.as Cr; See Pocket Guide App. C
TLV	Long-term value: 0.003* 0.5** mg/m ³ inh. fraction, *as Cr(III): A4, **metal

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

7440-02-0 Nickel	
PEL	Long-term value: 1 mg/m ³
REL	Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A
TLV	Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction, A5, BEI
13463-67-7 Titanium Dioxide	
PEL	Long-term value: 15* mg/m ³ *total dust
REL	See Pocket Guide App. A
TLV	Long-term value: 0.2* 2.5** mg/m ³ resp. fraction, *nanoscale, **finescale, A3
7439-96-5 Manganese	
PEL	Ceiling limit value: 5 mg/m ³ as Mn
REL	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³ fume, as Mn
TLV	Long-term value: 0.02* 0.1** mg/m ³ as Mn; A4, *respirable **inhalable fraction
7440-67-7 Zirconium	
PEL	Long-term value: 5 mg/m ³ as Zr
REL	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³ as Zr
TLV	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³ as Zr; A4
7439-98-7 Molybdenum	
PEL	Long-term value: 15* mg/m ³ *Total dust, as Mo
TLV	Long-term value: 10* 3** mg/m ³ as Mo; *inhalable fraction **respirable fraction
1344-28-1 Aluminum Oxide	
PEL	Long-term value: 15*; 5** mg/m ³ *Total dust; **Respirable fraction
REL	Long-term value: 10* 5** mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV	Long-term value: 1* mg/m ³ as Al; *as respirable fraction, A4
7631-86-9 Silicon Dioxide	
ACGH	Short-term value: 3 mg/m ³ Long-term value: 10 mg/m ³
IDLH	Short-term value: 3000 mg/m ³ Long-term value: 4 mg/m ³ IDLH: Immediately dangerous to life or health

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

TWA	Short-term value: 6 mg/m ³ Long-term value: 4 mg/m ³
7440-21-3 Silicon	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn
1314-23-4 Zirconium oxide	
PEL	Long-term value: 5 mg/m ³ as Zr
REL	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³ as Zr
TLV	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³ as Zr; A4
1317-95-9 Silica	
PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ / %SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *respirable particulate matter, A2
7429-90-5 Aluminium	
PEL	Short-term value: 5** mg/m ³ Long-term value: 15* mg/m ³ *Total dust; ** Respirable fraction
REL	Short-term value: 5** mg/m ³ Long-term value: 10* mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV	Long-term value: 1* mg/m ³ as Al; *as respirable fraction, A4
Ingredients with biological limit values:	
7440-47-3 Chromium	
BEI	0.7 µg/L urine end of shift at end of workweek Total chromium (population based)

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

7440-02-0 Nickel

BEI	5 µg/L urine post-shift at end of workweek Nickel (background)
	30 µg/L urine post-shift at end of workweek Nickel (background)

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**
- **Personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing and wash before reuse.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**



Suitable respiratory protective device recommended.

Use NIOSH approved or equivalent fume respirator or air supplied respirator when welding, brazing, cutting, grinding, or soldering in a confined space or general work area where local exhaust and/or ventilation does not keep exposure below the limits outlined in Section 8. Monitor the air quality inside the welder's helmet, and/or worker's breathing zone to determine if a respirator is required and the type needed.

- **Protection of hands:**



Protective gloves

- **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

- **Eye protection:**



Helmet or face shield

Wear a helmet or face shield with a filter lens around shade number 14. Adjust if needed by selecting the next lighter or darker shade number. See ANSI/ASC Z49.1 Section 4.2 or publication F2.2. Shield other workers by providing screens and flash goggles.

- **Body protection:**

Wear approved head, hand, and body protection, which help to prevent injury from radiation, sparks, and electrical shock. This would include wearing welder's gloves and a protective face shield and may include arm

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

protectors, apron, hats, shoulder protection, as well as dark, non-synthetic, substantial clothing. See ANSI Z49.1. Welders should be trained not to allow electrically live parts to contact the skin or wet clothing and gloves. The welders should insulate themselves from the work and ground and should not touch live electrical parts. Welders should not wear short sleeve shirts or short pants.

· **Limitation and supervision of exposure into the environment:** None

9 Physical and Chemical Properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Flux Coated Wire/Rod

Color:

Silver/gray wire covered by various colored fluxes

· Odor:

Odorless until used

· Odor threshold:

Not determined.

· pH-value:

Not applicable.

· Change in condition

Melting point/Melting range:

Not determined.

· Flash point:

None

· Flammability (solid, gaseous):

Not determined.

· Ignition temperature:

Not applicable

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not self-igniting.

· Danger of explosion:

Product does not present an explosion hazard.

· Explosion limits:

Lower:

Not determined.

Upper:

Not determined.

· Vapor pressure:

Not applicable.

· Density:

Not determined.

· Relative density:

Not determined.

· Vapor density:

Not applicable.

· Evaporation rate:

Not applicable.

· Solubility in / Miscibility with:

Water:

Insoluble.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

Dynamic:

Not applicable.

Kinematic:

Not applicable.

· Solvent content:

VOC content:

0.00 %

Solids content:

100.0 %

· Other information:

No further relevant information available.

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

10 Stability and Reactivity

- **Reactivity:**

Stable under normal conditions.

May react violently or explosively on contact with water. Will react with water or steam to product hydrogen.

Incompatible (violent reactions) with chlorine, fluorine, oxidizers, calcium, carbide, alkali carbonates, iodine pentafluoride, cobaltic fluoride, rubidium carbide, MnF₃, nitrosyl fluoride, AgF. Mixtures of cesium acetylide with silicon react vigorously on heating. Rubidium acetylide reacts vigorously with silicon on warming.

- **Chemical stability:** Stable under normal conditions.

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

- **Possibility of hazardous reactions:**

May react violently or explosively on contact with water. Will react with water or steam to product hydrogen

Incompatible (violent reactions) with chlorine, fluorine, oxidizers, calcium, carbide, alkali carbonates, iodine pentafluoride, cobaltic fluoride, rubidium carbide, MnF₃, nitrosyl fluoride, AgF. Mixtures of cesium acetylide with silicon react vigorously on heating. Rubidium acetylide reacts vigorously with silicon on warming.

Contact with acids or strong bases may cause generation of gas.

- **Conditions to avoid:** No further relevant information available.

- **Incompatible materials:**

Incompatible (violent reactions) with chlorine, fluorine, oxidizers, calcium, carbide, alkali carbonates, iodine pentafluoride, cobaltic fluoride, rubidium carbide, MnF₃, nitrosyl fluoride, AgF.

Strong acids, strong bases, strong oxidizing agents and strong reducing agents.

- **Hazardous decomposition products:**

Toxic chromium oxide fumes.

Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the processes and procedures followed, and the welding consumables used. Other conditions that also influence the composition and quantity of fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, or galvanizing), the number of welders in operation and the volume of the work area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume, and the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing procedures). When the electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 8. Fume and gas decomposition, and not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration. Also, new compounds not in the electrodes may form. The known gases and fumes that may form during welding or cutting and their exposure limits are noted in the list in Section 11 below. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 8, plus those from the base metal and coating, etc. as noted above. Chlorinated solvents may be decomposed into toxic gases such as phosgene.

It is understood, however, that the elements and/or oxides to be mentioned are virtually always present as complex oxides and not as metals (See "Characterization of Arc Welding Fume", from the American Welding Society). The elements or oxides listed Section 8 correspond to the ACGIH categories found in "Threshold Limit Values for Chemical Substances and Physical Agents" listed in Section 8. Some products will also contain: Oxides of iron, carbon, chromium, nickel, molybdenum, manganese, silicon, titanium, aluminum, zirconium, and fluorides and ozone. Some elements or compounds may exceed their PELs/TLVs before the total fumes exceed 5 mg/m³.

11 Toxicological Information

- **Information on toxicological effects:**

Effects of Over-Exposure: Electric arc welding may create one or more of the following health hazards:

- ARC RAYS can injure eyes and burn skin. Incidences of skin cancer have been reported.
- ELECTRIC SHOCK can kill.
- FUMES AND GASES GENERATED FROM WELDING can be dangerous to your health.
- PRIMARY ROUTES OF ENTRY are the respiratory system, eyes, skin, and/or indigestion.

(Contd. on page 12)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

- NOISE can damage hearing.

Short-term (acute) over-exposure effects:

- WELDING FUMES may result in discomfort, such as dizziness, nausea, or dryness or irritation of the nose, throat, or eyes.
- ALUMINUM OXIDE may cause irritation of the respiratory system.
- FLUORIDES, FLUORIDE COMPOUNDS may cause skin and eye burns, pulmonary edema, and bronchitis.
- IRON, IRON OXIDE have no known effects. Treat as a nuisance dust or fume.
- MANGANESE, MANGANESE COMPOUNDS may cause metal fume fever, characterized by irritation of the throat, vomiting, nausea, fever, body aches, and chills. Recovery is generally complete within 48 hours of overexposure.
- MOLYBDENUM may cause irritation of the eyes, nose, and throat.
- NICKEL, NICKEL COMPOUNDS may cause metallic taste, nausea, tightness in chest, fever, and allergic reactions.
- SILICA (amorphous) dust and fumes may cause irritation of the respiratory system, skin, and eyes.
- TITANIUM DIOXIDE may cause irritation of the respiratory system.

Long-term (chronic) over-exposure effects:

- WELDING FUMES in excess levels may cause bronchial asthma, lung fibrosis, pneumoconiosis, or 'siderosis.' Overexposure to air contaminants may lead to their accumulation in the lungs, a condition which may be seen as dense areas on chest x-rays. The severity of the change is proportional to the length of exposure. The changes seen are not necessarily associated with symptoms or signs of reduced lung function or disease. In addition, the changes on X-rays may be caused by non-work factors such as smoking, etc.
- ALUMINUM OXIDE may cause pulmonary fibrosis and emphysema.
- FLUORIDES may cause serious bone erosion (osteoporosis) and mottling of teeth.
- IRON, IRON OXIDE may cause siderosis or deposits of iron in the lungs, which is believed to affect pulmonary function. Lungs will clear in time when exposure to iron fumes and its compounds ceases. Iron and magnetite (Fe₃O₄) are not regarded as fibrogenic materials.
- MANGANESE, MANGANESE COMPOUNDS may cause central nervous system effects referred to as 'manganism.' Symptoms include languor, sleepiness, muscular weakness, emotional disturbances, spastic gait, and tremors. Behavioral changes and changes in handwriting may also appear. These effects are irreversible. Employees overexposed to manganese should receive regular medical examinations for early detection of manganism.
- MOLYBDENUM prolonged overexposure may result in loss of appetite, weight loss, loss of muscle coordination, difficulty in breathing, and anemia.
- NICKEL, NICKEL COMPOUNDS may lung fibrosis or pneumoconiosis. Studies of nickel refinery workers indicated a higher incidence of lung and nasal cancers.
- SILICA (respirable crystalline silica) overexposure may result in silicosis. Respirable crystalline silica is a known human carcinogen. SILICA (amorphous) long term overexposure may cause pneumoconiosis. Noncrystalline forms of silica (amorphous silica) are considered to have little fibrotic potential.
- TITANIUM DIOXIDE may cause pulmonary irritation and slight fibrosis.

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

7440-47-3 Chromium

Inhalative	LC50/96 hours	14.3 mg/l (Cyprinus carpio)
------------	---------------	-----------------------------

13463-67-7 Titanium Dioxide

Oral	LD50	>10,000 mg/kg (Rat)
Dermal	LD50	>10,000 mg/kg (Rabbit)

(Contd. on page 12)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

Inhalative	LC50/4 h	>6.82 mg/l (Rat)
7439-96-5 Manganese		
Oral	LD50	9,000 mg/kg (Rat)
7439-98-7 Molybdenum		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
Inhalative	LC50/4 h	800 mg/l (Trout) >5.84 mg/l (Rat)
1344-28-1 Aluminum Oxide		
Oral	LD50	>10,000 mg/kg (Rat)
Inhalative	LC50/4 h	>2.6 mg/l (Rat)
7631-86-9 Silicon Dioxide		
Oral	LD50	10,000 mg/kg (Rat) (OECD 401)
Dermal	LD50	5,000 mg/kg (Rabbit) (OECD 402)
Inhalative	LC50/4 h	>140->2,000 mg/l (Rat) (OCED 403) Maximum attainable concentration, mortality does not appear. 10,000 mg/l (Zebra fish) (OECD 203)
7440-21-3 Silicon		
Oral	LD50	3,160 mg/kg (Rat)
1314-23-4 Zirconium oxide		
Inhalative	LC50/96 hours	>100 mg/l (Zebra fish)
7429-90-5 Aluminium		
Oral	LD50	>2,000 mg/kg (Rat)
Inhalative	LC50/4 h	888 mg/l (Rat)

• **Primary irritant effect:**

• **On the skin:**

Irritant to skin and mucous membranes.

May cause an allergic skin reaction.

• **On the eye:** Irritating effect.

• **Sensitization:** Sensitization possible through skin contact.

• **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

• **Carcinogenic categories:**

• **IARC (International Agency for Research on Cancer):**

(a) Although IARC has classified titanium dioxide as possible carcinogenic to human (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is bound to other materials, such as in cosmetics or in paints."

(b) OSHA does not regulate Titanium Dioxide as a carcinogen. However, under 29 CFR 1910.1200 the SDS must convey the fact that Titanium Dioxide is a potential carcinogen to rats.

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

(Contd. on page 14)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

7440-47-3	Chromium	3
7440-02-0	Nickel	2B
13463-67-7	Titanium Dioxide	2B
7631-86-9	Silicon Dioxide	3
1317-95-9	Silica	1
· NTP (National Toxicology Program):		
7440-02-0	Nickel	R
· OSHA-Ca (Occupational Safety & Health Administration):		
None of the ingredients are listed.		

12 Ecological Information

· **Toxicity:**

· **Aquatic toxicity:**

7440-47-3 Chromium

EC50 0.07 mg/l (Water flea)

7440-02-0 Nickel

EC50 1 mg/l (Water flea)

13463-67-7 Titanium Dioxide

EC50 >1,000 mg/l (Water flea)

7439-96-5 Manganese

EC50 40 mg/l (Water flea)

7631-86-9 Silicon Dioxide

EC50 >1,000 mg/l (Daphnia) (OECD 202)

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment:**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household waste. Do not allow product to reach sewage system.

Observe all federal, state and local environmental regulations when disposing of this material.

· **Uncleaned packaging**

· **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 15)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

14 Transport Information

- **UN-Number:**
· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material
- **UN proper shipping name:**
· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material
- **Transport hazard class(es):**
· DOT, ADR/ADN, ADN, IMDG, IATA
- **Class:** Non-Regulated Material
- **Packing group:**
· DOT, ADR/ADN, IMDG, IATA Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

7440-47-3 Chromium

7440-02-0 Nickel

7439-96-5 Manganese

1344-28-1 Aluminum Oxide

7429-90-5 Aluminium

· TSCA (Toxic Substances Control Act):

7439-89-6	Iron	ACTIVE
7440-47-3	Chromium	ACTIVE
7440-02-0	Nickel	ACTIVE
13463-67-7	Titanium Dioxide	ACTIVE
7440-32-6	Titanium	ACTIVE
7439-96-5	Manganese	ACTIVE
7440-67-7	Zirconium	ACTIVE
7439-98-7	Molybdenum	ACTIVE
1344-28-1	Aluminum Oxide	ACTIVE
7631-86-9	Silicon Dioxide	ACTIVE
7440-21-3	Silicon	ACTIVE
1314-23-4	Zirconium oxide	ACTIVE
7429-90-5	Aluminium	ACTIVE
7440-44-0	Carbon Fiber	ACTIVE

· Hazardous Air Pollutants

7439-96-5 Manganese

(Contd. on page 15)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

· **California Proposition 65:**



WARNING: This product can expose you to chemicals including the listed chemicals which are known to the State of California to cause cancer, birth defects and/or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

· Chemicals known to cause cancer:		
7440-02-0	Nickel	
13463-67-7	Titanium Dioxide	
· Chemicals known to cause reproductive toxicity for females:		
None of the ingredients are listed.		
· Chemicals known to cause reproductive toxicity for males:		
None of the ingredients are listed.		
· Chemicals known to cause developmental toxicity:		
None of the ingredients are listed.		
· New Jersey Right-to-Know List:		
7440-47-3	Chromium	
7440-02-0	Nickel	
13463-67-7	Titanium Dioxide	
7440-32-6	Titanium	
7439-96-5	Manganese	
7440-67-7	Zirconium	
7439-98-7	Molybdenum	
1344-28-1	Aluminum Oxide	
7440-21-3	Silicon	
1317-95-9	Silica	
7429-90-5	Aluminium	
· New Jersey Special Hazardous Substance List:		
7440-47-3	Chromium	F3
7440-02-0	Nickel	CA
7440-32-6	Titanium	F3, R1
7439-96-5	Manganese	F3, R1
7440-67-7	Zirconium	F4, R1
7440-21-3	Silicon	F3
1317-95-9	Silica	CA
7429-90-5	Aluminium	F3, R1
· Pennsylvania Right-to-Know List:		
7440-47-3	Chromium	
7440-02-0	Nickel	
13463-67-7	Titanium Dioxide	
7439-96-5	Manganese	
7440-67-7	Zirconium	
7439-98-7	Molybdenum	

(Contd. on page 16)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

1344-28-1	Aluminum Oxide	
7631-86-9	Silicon Dioxide	
7440-21-3	Silicon	
1317-95-9	Silica	
7429-90-5	Aluminium	
· Pennsylvania Special Hazardous Substance List:		
7440-47-3	Chromium	ES
7440-02-0	Nickel	ES
7439-96-5	Manganese	E
1344-28-1	Aluminum Oxide	E
7429-90-5	Aluminium	E

· Carcinogenic categories:

· EPA (Environmental Protection Agency):		
7440-47-3	Chromium	D
7439-96-5	Manganese	D

· TLV (Threshold Limit Value established by ACGIH):

7440-47-3	Chromium	A4
7440-02-0	Nickel	A5
13463-67-7	Titanium Dioxide	A4
7440-67-7	Zirconium	A4
7439-98-7	Molybdenum	A3
1344-28-1	Aluminum Oxide	A4
1314-23-4	Zirconium oxide	A4
1317-95-9	Silica	A2
7429-90-5	Aluminium	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health):

7440-02-0	Nickel	
13463-67-7	Titanium Dioxide	
1317-95-9	Silica	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



· Signal word: Danger

· Hazard-determining components of labeling:

Nickel
Titanium Dioxide
Titanium
Silica

· Hazard statements:

H320 Causes eye irritation.

(Contd. on page 17)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

H317 May cause an allergic skin reaction.

H350 May cause cancer. Route of exposure: Inhalation.

H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 If on skin: Wash with plenty of water.
- P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

Pinnacle Alloys urges each end user and recipient of this SDS to study it carefully. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product. This information is believed to be accurate as of the revision date shown above. However, no warranty, expressed or implied, is given. Because the conditions or methods of use are beyond Pinnacle Alloys' control, we assume no liability resulting from the use of this product. Regulatory requirements are subject to change and may differ between various locations. Compliance with all applicable Federal, State, Provincial, and Local laws and regulations remain the responsibility of the user.

Contact:

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative

(Contd. on page 19)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/13/2022

Reviewed on 09/13/2022

Trade Name: Stainless Steel Flux Cored and Metal Cored Welding Electrodes and Rods

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Solids 2: Flammable solids – Category 2

Pyrophoric Solids 1: Pyrophoric solids – Category 1

Substances and mixtures which, in contact with water, emit flammable gases 1: Substances and mixtures which in contact with water emit flammable gases – Category 1

Acute Toxicity - Oral 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 1A: Carcinogenicity – Category 1A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

*** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106