

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

* 1 Identification

- **Product Identifier**
- **Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding**
- **Product Number:**
 - Specification: A5.5
 - Classification: E10018-D2, E10018M, E11018M, E12018M, E7018-A1, E7018-B2L, E8018-B2, E8018-B2L, E8018-B3L, E8018-B6, E8018-B8, E8018-C1, E8018-C2, E8018-C3, E9018-B3L, E9018-B9, E9018M
 - Low hydrogen, low alloy steel
- **Relevant identified uses of the substance or mixture and uses advised against:**
 - For professional use only. Use according to manufacturer's specification.
- **Product Description:** Low hydrogen, low-alloy steel welding electrodes.
- **Application of the substance / the mixture:** Industry specific application.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
 - SOWESCO I, LLC
 - 9384 Wallisville Road
 - Houston, TX 77013
 - Telephone: 800-856-9353
- **Emergency telephone number:** 713-688-9353

2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Health hazard

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger
- **Hazard-determining components of labeling:**
 - Iron
 - Potassium Silicate

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

Silica

Nickel

Hazard statements:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H335 May cause respiratory irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

15.5 % of the mixture consists of component(s) of unknown toxicity.

Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme**NFPA ratings (scale 0 - 4)**

Health = 3

Fire = 0

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = *3

Fire = 0

Physical Hazard = 0

Hazard(s) not otherwise classified (HNOC): None known**3 Composition/Information on Ingredients****Chemical characterization: Mixtures****Description:** Mixture of substances listed below with non-hazardous additions.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

· Dangerous Components:		
CAS: 7439-89-6 RTECS: NO 4565500	Iron ⚠ Flam. Sol. 2, H228; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320; Combustible Dust	40-60%
CAS: 7789-75-5 RTECS: EW 1760000	Calcium fluoride ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	2-12%
CAS: 9004-34-6	Cellulose	2-12%
CAS: 7440-47-3 RTECS: GB 4200000	Chromium	2-12%
CAS: 1317-95-9	Silica ⚠ Carc. 1A, H350; ⚠ STOT SE 3, H335	2-12%
CAS: 1312-76-1	Potassium Silicate ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335	2-12%
CAS: 7439-96-5 RTECS: OO 9275000	Manganese ⚠ Pyr. Sol. 1, H250; Water-react. 1, H260	≤2.5%
CAS: 7440-02-0	Nickel ⚠ Carc. 2, H351; STOT RE 1, H372; ⚠ Skin Sens. 1, H317	≤2.5%
CAS: 7440-21-3	Silicon ⚠ Flam. Sol. 2, H228; ⚠ Acute Tox. 4, H302; Eye Irrit. 2B, H320; Combustible Dust	≤2.5%
CAS: 13463-67-7	Titanium Dioxide ⚠ Carc. 2, H351	≤2.5%
CAS: 7439-98-7 RTECS: QA 4680000	Molybdenum	≤2.5%
CAS: 7631-86-9	Silicon Dioxide ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	≤2.5%
CAS: 546-93-0	Magnesium Carbonate	≤2.5%
CAS: 1313-59-3	Sodium oxide ⚠ Ox. Sol. 1, H271; ⚠ Skin Corr. 1C, H314	≤2.5%
CAS: 12136-45-7	Dipotassium Oxide ⚠ Water-react. 3, H261; ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318	≤2.5%

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (j) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

Note: Certain chemical constituents listed in Section 3 may vary depending upon the Classification of the Low-Alloy Steel Electrodes for Shielded Metal Arc Welding products.

4 First-Aid Measures**· Description of first aid measures****· General information:**

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in the side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

- **After eye contact:**

Do NOT rub eyes. Immediately rinse opened eye(s) for at least 15 minutes under running water, lifting upper and lower lids occasionally. If symptoms persist, consult a physician.
If easy to do so, remove contact lenses if worn.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.
Do not induce vomiting without medical advice.
If swallowed and symptoms occur, consult a doctor.

- **Information for doctor**

- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

5 Fire-Fighting Measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire fighting measures that suit the environment.

- **For safety reasons unsuitable extinguishing agents:** No further relevant information.

- **Special hazards arising from the substance or mixture:**

Amorphous or crystalline silicon both react exothermically when heated with alkali-metal carbonates attaining incandescence and evolving carbon monoxide.

Material in powder form, capable of creating a dust explosion. Mixture of silicon, aluminum, and lead oxide explodes when heated.

Moderate fire hazard when it is in the form of a dust (powder) and burns rapidly when heated in flame. Chromium is attacked vigorously by fused potassium chlorate producing vivid incandescence. Pyrophoric chromium unites with nitric oxide with incandescence. Incandescent reaction with nitrogen oxide or sulfur dioxide.

Special Remarks on Explosion Hazards:

Powdered Chromium metal +fused ammonium nitrate may react violently or explosively. Powdered Chromium will explode spontaneously in air.

If incinerated, product will release the following toxic fumes: Oxides of carbon, chromium, calcium, iron, magnesium, manganese, molybdenum, nickel, potassium, silicon, sodium, strontium, titanium, and fluorides and ozone.

- **Advice for firefighters**

- **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

- **Additional information:**

These items are not reactive, flammable, or explosive and essentially not hazardous at ambient temperatures. Welding arcs and sparks can ignite combustibles and flammable products. If involved in a fire, these products may generate a variety of metal oxides. Emergency responders must wear personal protection equipment suitable for the situation. Use the extinguishing media recommended for the burning materials and fire situation. See ANSI Z49.1 "Safety in Welding and Cutting" and "Safe Practices" Code: SP, published by the American Welding Society.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

- **Environmental precautions:** Do not allow to enter sewers/surface or ground water.
- **Methods and material for containment and cleaning up:**
Pick up mechanically.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Dispose of the collected material according to regulations.
Flammable solid. Stop leak if without risk. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
7439-89-6	Iron	3.2 mg/m ³
7789-75-5	Calcium fluoride	15 mg/m ³
7440-47-3	Chromium	1.5 mg/m ³
1312-76-1	Potassium Silicate	30 mg/m ³
7439-96-5	Manganese	3 mg/m ³
7440-02-0	Nickel	4.5 mg/m ³
7440-21-3	Silicon	45 mg/m ³
13463-67-7	Titanium Dioxide	30 mg/m ³
7439-98-7	Molybdenum	30 mg/m ³
7631-86-9	Silicon Dioxide	18 mg/m ³
546-93-0	Magnesium Carbonate	45 mg/m ³
1313-59-3	Sodium oxide	0.5 mg/m ³
12136-45-7	Dipotassium Oxide	0.18 mg/m ³
· PAC-2:		
7439-89-6	Iron	35 mg/m ³
7789-75-5	Calcium fluoride	170 mg/m ³
7440-47-3	Chromium	17 mg/m ³
1312-76-1	Potassium Silicate	330 mg/m ³
7439-96-5	Manganese	5 mg/m ³
7440-02-0	Nickel	50 mg/m ³
7440-21-3	Silicon	100 mg/m ³
13463-67-7	Titanium Dioxide	330 mg/m ³
7439-98-7	Molybdenum	330 mg/m ³
7631-86-9	Silicon Dioxide	740 mg/m ³
546-93-0	Magnesium Carbonate	260 mg/m ³
1313-59-3	Sodium oxide	5 mg/m ³
12136-45-7	Dipotassium Oxide	2 mg/m ³
· PAC-3:		
7439-89-6	Iron	150 mg/m ³
7789-75-5	Calcium fluoride	1,000 mg/m ³
7440-47-3	Chromium	99 mg/m ³

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

1312-76-1	Potassium Silicate	2,000 mg/m ³
7439-96-5	Manganese	1,800 mg/m ³
7440-02-0	Nickel	99 mg/m ³
7440-21-3	Silicon	630 mg/m ³
13463-67-7	Titanium Dioxide	2,000 mg/m ³
7439-98-7	Molybdenum	2,000 mg/m ³
7631-86-9	Silicon Dioxide	4,500 mg/m ³
546-93-0	Magnesium Carbonate	1,600 mg/m ³
1313-59-3	Sodium oxide	50 mg/m ³
12136-45-7	Dipotassium Oxide	54 mg/m ³

7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**
Avoid creating and breathing dust/fume/gas/mist/vapors/spray.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
Store away from strong acids, strong bases, strong oxidizing agents and strong reducing agents.
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in the original container.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.
- **Components with occupational exposure limits:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

7789-75-5 Calcium fluoride	
PEL	Long-term value: 2.5 mg/m ³ as F
REL	Long-term value: 2.5 mg/m ³ as F
TLV	Long-term value: 2.5 mg/m ³ as F, BEI
9004-34-6 Cellulose	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 10 mg/m ³
7440-47-3 Chromium	
REL	Long-term value: 1 mg/m ³
REL	Long-term value: 0.5* mg/m ³ *metal+inorg.compds.as Cr; See Pocket Guide App. C
TLV	Long-term value: 0.003* 0.5** mg/m ³ inh. fraction, *as Cr(III), **metal
1317-95-9 Silica	
REL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	TLV withdrawn
7439-96-5 Manganese	
REL	Ceiling limit value: 5 mg/m ³ as Mn
REL	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³ fume, as Mn
TLV	Long-term value: 0.02* 0.1** mg/m ³ as Mn; *respirable **inhalable fraction
7440-02-0 Nickel	
REL	Long-term value: 1 mg/m ³
REL	Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A
TLV	Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction
7440-21-3 Silicon	
REL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn
13463-67-7 Titanium Dioxide	
REL	Long-term value: 15* mg/m ³ *total dust
REL	See Pocket Guide App. A
TLV	Long-term value: 10 mg/m ³
7439-98-7 Molybdenum	
REL	Long-term value: 15* mg/m ³ *Total dust, as Mo
TLV	Long-term value: 10* 3** mg/m ³ as Mo; *inhalable fraction ** respirable fraction

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

7631-86-9 Silicon Dioxide	
ACGH	Short-term value: 3 mg/m ³ Long-term value: 10 mg/m ³
IDLH	Short-term value: 3000 mg/m ³ Long-term value: 4 mg/m ³ IDLH: Immediately dangerous to life or health
TWA	Short-term value: 6 mg/m ³ Long-term value: 4 mg/m ³
546-93-0 Magnesium Carbonate	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn
· Ingredients with biological limit values:	
7789-75-5 Calcium fluoride	
BEI	2 mg/L urine prior to shift Fluoride (background, nonspecific)
	3 mg/L urine end of shift Fluoride (background, nonspecific)

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



Suitable respiratory protective device recommended.

Use NIOSH approved or equivalent fume respirator or air supplied respirator when welding, brazing, cutting, grinding, or soldering in a confined space or general work area where local exhaust and/or ventilation does not keep exposure below the limits outlined in Section 8. Monitor the air quality inside the welder's helmet, and/or worker's breathing zone to determine if a respirator is required and the type needed.

· **Protection of hands:**



Protective gloves

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Goggles with face-shield

Wear a helmet or face shield with a filter lens around shade number 14. Adjust if needed by selecting the next lighter or darker shade number. See ANSI/ASC Z49.1 Section 4.2 or publication F2.2. Shield other workers by providing screens and flash goggles.

· **Body protection:**



Protective work clothing

Wear approved head, hand, and body protection, which help to prevent injury from radiation, sparks, and electrical shock. This would include wearing welder's gloves and a protective face shield and may include arm protectors, apron, hats, shoulder protection, as well as dark, non-synthetic, substantial clothing. See ANSI Z49.1. Welders should be trained not to allow electrically live parts to contact the skin or wet clothing and gloves. The welders should insulate themselves from the work and ground and should not touch live electrical parts. Welders should not wear short sleeve shirts or short pants.

· **Limitation and supervision of exposure into the environment:** None

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Flux Coated Wire/Rod

Color:

Silver/gray wire covered by various colored fluxes

· **Odor:**

Odorless until used

· **Odor threshold:**

Not determined.

· **pH-value:**

Not applicable.

· **Change in condition**

Melting point/Melting range:

Not determined.

Boiling point/Boiling range:

Not determined.

· **Flash point:**

None

· **Flammability (solid, gaseous):**

Not determined.

· **Ignition temperature:**

Not applicable

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
 - Lower:** Not determined.
 - Upper:** Not determined.
- **Vapor pressure:** Not applicable.
- **Density:**
 - Relative density:** Not determined.
 - Vapor density:** Not applicable.
 - Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
 - Water:** Insoluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not applicable.
 - Kinematic:** Not applicable.
- **Solvent content:**
 - VOC content:** 0.00 %
 - Solids content:** 100.0 %
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** Stable under normal conditions.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** Contact with acids or strong bases may cause generation of gas.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Strong acids, strong bases, strong oxidizing agents and strong reducing agents.
- **Hazardous decomposition products:**

Toxic chromium oxide fumes.

Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the processes and procedures followed, and the welding consumables used. Other conditions that also influence the composition and quantity of fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, or galvanizing), the number of welders in operation and the volume of the work area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume, and the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing procedures). When the electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 8. Fume and gas decomposition, and not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration. Also, new compounds not in the electrodes may form. The known gases and fumes that may form during welding or cutting and their exposure limits are noted in the list in Section 11 below. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 8, plus those from the base metal and coating, etc. as noted above. Chlorinated solvents may be decomposed into toxic gases such as phosgene.

It is understood, however, that the elements and/or oxides to be mentioned are virtually always present as complex oxides and not as metals (See "Characterization of Arc Welding Fume", from the American Welding

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

Society). The elements or oxides listed Section 8 correspond to the ACGIH categories found in "Threshold Limit Values for Chemical Substances and Physical Agents" listed in Section 8. Some products will also contain: carbon, chromium, calcium, iron, magnesium, manganese, molybdenum, nickel, potassium, silicon, sodium, strontium, titanium, and fluorides. Some elements or compounds may exceed their PELs/TLVs before the total fumes exceed 5 mg/m³.

11 Toxicological Information

· Information on toxicological effects:

Effects of Over-Exposure: Electric arc welding may create one or more of the following health hazards:

- ARC RAYS can injure eyes and burn skin. Incidences of skin cancer have been reported.
- ELECTRIC SHOCK can kill.
- FUMES AND GASES GENERATED FROM WELDING can be dangerous to your health.
- PRIMARY ROUTES OF ENTRY are the respiratory system, eyes, skin, and/or indigestion.
- NOISE can damage hearing.

Short-term (acute) over-exposure effects:

- WELDING FUMES may result in discomfort, such as dizziness, nausea, or dryness or irritation of the nose, throat, or eyes.
- CALCIUM OXIDE dust or fumes may cause irritation of the respiratory system, skin, and eyes.
- FLUORIDES, FLUORIDE COMPOUNDS may cause skin and eye burns, pulmonary edema, and bronchitis.
- IRON, IRON OXIDE have no known effects. Treat as a nuisance dust or fume.
- MANGANESE, MANGANESE COMPOUNDS may cause metal fume fever, characterized by irritation of the throat, vomiting, nausea, fever, body aches, and chills. Recovery is generally complete within 48 hours of overexposure.
- MOLYBDENUM may cause irritation of the eyes, nose, and throat.
- NICKEL, NICKEL COMPOUNDS may cause metallic taste, nausea, tightness in chest, fever, and allergic reactions.
- POTASSIUM OXIDE dust or fumes may cause irritation of the respiratory system, skin, and eyes.
- SILICA (amorphous) dust and fumes may cause irritation of the respiratory system, skin, and eyes.
- TITANIUM DIOXIDE may cause irritation of the respiratory system.

Long-term (chronic) over-exposure effects:

- WELDING FUMES in excess levels may cause bronchial asthma, lung fibrosis, pneumoconiosis, or 'siderosis.' Overexposure to air contaminants may lead to their accumulation in the lungs, a condition which may be seen as dense areas on chest x-rays. The severity of the change is proportional to the length of exposure. The changes seen are not necessarily associated with symptoms or signs of reduced lung function or disease. In addition, the changes on X-rays may be caused by non-work factors such as smoking, etc.
- CALCIUM OXIDE prolonged overexposure may cause ulceration of the skin and perforation of the nasal septum, dermatitis, and pneumonia.
- FLUORIDES may cause serious bone erosion (osteoporosis) and mottling of teeth.
- IRON, IRON OXIDE may cause siderosis or deposits of iron in the lungs, which is believed to affect pulmonary function. Lungs will clear in time when exposure to iron fumes and its compounds ceases. Iron and magnetite (Fe₃O₄) are not regarded as fibrogenic materials.
- MANGANESE, MANGANESE COMPOUNDS may cause central nervous system effects referred to as 'manganism.' Symptoms include languor, sleepiness, muscular weakness, emotional disturbances, spastic gait, and tremors. Behavioral changes and changes in handwriting may also appear. These effects are irreversible. Employees overexposed to manganese should receive regular medical examinations for early detection of manganism.
- MOLYBDENUM prolonged overexposure may result in loss of appetite, weight loss, loss of muscle coordination, difficulty in breathing, and anemia.
- NICKEL, NICKEL COMPOUNDS may lung fibrosis or pneumoconiosis. Studies of nickel refinery workers indicated a higher incidence of lung and nasal cancers.
- POTASSIUM OXIDE prolonged overexposure may cause ulceration of the skin and perforation of the nasal

(Contd. on page 12)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

septum, dermatitis, and pneumonia.

- SILICA (respirable crystalline silica) overexposure may result in silicosis. Respirable crystalline silica is a known human carcinogen. SILICA (amorphous) long term overexposure may cause pneumoconiosis. Noncrystalline forms of silica (amorphous silica) are considered to have little fibrotic potential.
- TITANIUM DIOXIDE may cause pulmonary irritation and slight fibrosis.

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

7439-89-6 Iron		
Oral	LD50	7,500 mg/kg (Rat)
7789-75-5 Calcium fluoride		
Oral	LD50	4,250 mg/kg (Rat)
9004-34-6 Cellulose		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)
7440-47-3 Chromium		
Inhalative	LC50/96 hours	14.3 mg/l (Cyprinus carpio)
7439-96-5 Manganese		
Oral	LD50	9,000 mg/kg (Rat)
7440-21-3 Silicon		
Oral	LD50	3,160 mg/kg (Rat)
13463-67-7 Titanium Dioxide		
Oral	LD50	>10,000 mg/kg (Rat)
Dermal	LD50	>10,000 mg/kg (Rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (Rat)
7439-98-7 Molybdenum		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
Inhalative	LC50/4 h	800 mg/l (Trout) >5.84 mg/l (Rat)
7631-86-9 Silicon Dioxide		
Oral	LD50	10,000 mg/kg (Rat) (OECD 401)
Dermal	LD50	5,000 mg/kg (Rabbit) (OECD 402)
Inhalative	LC50/4 h	>140->2,000 mg/l (Rat) (OCED 403) Maximum attainable concentration, mortality does not appear. 10,000 mg/l (Zebra fish) (OECD 203)

· **Primary irritant effect:**

· **On the skin:**

- Strong caustic effect on skin and mucous membranes.
- Irritant to skin and mucous membranes.
- May cause an allergic skin reaction.

· **On the eye:**

- Strong irritant with the danger of severe eye injury.
- Corrosive effect.
- Causes serious eye irritation.

· **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 13)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding**Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic categories:**IARC (International Agency for Research on Cancer):**

(a) Although IARC has classified titanium dioxide as possible carcinogenic to human (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is bound to other materials, such as in cosmetics or in paints."

(b) OSHA does not regulate Titanium Dioxide as a carcinogen. However, under 29 CFR 1910.1200 the SDS must convey the fact that Titanium Dioxide is a potential carcinogen to rats.

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

7789-75-5	Calcium fluoride	3
7440-47-3	Chromium	3
1317-95-9	Silica	1
7440-02-0	Nickel	2B
13463-67-7	Titanium Dioxide	2B
7631-86-9	Silicon Dioxide	3

NTP (National Toxicology Program):

7440-02-0 Nickel

R

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

12 Ecological Information**Toxicity:****Aquatic toxicity:****7440-47-3 Chromium**

EC50 0.07 mg/l (Water flea)

7439-96-5 Manganese

EC50 40 mg/l (Water flea)

7440-02-0 Nickel

EC50 1 mg/l (Water flea)

13463-67-7 Titanium Dioxide

EC50 >1,000 mg/l (Water flea)

7631-86-9 Silicon Dioxide

EC50 >1,000 mg/l (Daphnia) (OECD 202)

Persistence and degradability: No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

(Contd. on page 14)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding· **Additional ecological information:**· **General notes:**

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment:**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Other adverse effects:** No further relevant information available.**13 Disposal Considerations**· **Waste treatment methods**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

· **Uncleaned packaging**· **Recommendation:** Disposal must be made according to official regulations.**14 Transport Information**· **UN-Number:**· **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material· **UN proper shipping name:**· **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material· **Transport hazard class(es):**· **DOT, ADR/ADN, ADN, IMDG, IATA**· **Class:** Non-Regulated Material· **Packing group:**· **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material· **Environmental hazards:** Not applicable.· **Special precautions for user:** Not applicable.· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.· **UN "Model Regulation":** Non-Regulated Material**15 Regulatory Information**· **Safety, health and environmental regulations/legislation specific for the substance or mixture:**· **SARA (Superfund Amendments and Reauthorization):**· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

7440-47-3 Chromium

7439-96-5 Manganese

7440-02-0 Nickel

· **TSCA (Toxic Substances Control Act):**

7439-89-6 Iron

ACTIVE

7789-75-5 Calcium fluoride

ACTIVE

9004-34-6 Cellulose

ACTIVE

7440-47-3 Chromium

ACTIVE

(Contd. on page 15)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

1312-76-1	Potassium Silicate	ACTIVE
7439-96-5	Manganese	ACTIVE
7440-02-0	Nickel	ACTIVE
7440-21-3	Silicon	ACTIVE
13463-67-7	Titanium Dioxide	ACTIVE
7439-98-7	Molybdenum	ACTIVE
7631-86-9	Silicon Dioxide	ACTIVE
546-93-0	Magnesium Carbonate	ACTIVE
1313-59-3	Sodium oxide	ACTIVE
12136-45-7	Dipotassium Oxide	ACTIVE

· Hazardous Air Pollutants

7439-96-5 Manganese

· California Proposition 65:

WARNING: This product can expose you to chemicals including the listed chemicals which are known to the State of California to cause cancer, birth defects and/or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

· Chemicals known to cause cancer:

7440-02-0 Nickel

13463-67-7 Titanium Dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· New Jersey Right-to-Know List:

9004-34-6 Cellulose

7440-47-3 Chromium

1317-95-9 Silica

7439-96-5 Manganese

7440-02-0 Nickel

7440-21-3 Silicon

13463-67-7 Titanium Dioxide

7439-98-7 Molybdenum

546-93-0 Magnesium Carbonate

12136-45-7 Dipotassium Oxide

· New Jersey Special Hazardous Substance List:

7440-47-3 Chromium

F3

1317-95-9 Silica

CA

7439-96-5 Manganese

F3, R1

7440-02-0 Nickel

CA

7440-21-3 Silicon

F3

(Contd. on page 16)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

12136-45-7	Dipotassium Oxide	CO, R2
------------	-------------------	--------

· Pennsylvania Right-to-Know List:

9004-34-6	Cellulose	
7440-47-3	Chromium	
1317-95-9	Silica	
7439-96-5	Manganese	
7440-02-0	Nickel	
7440-21-3	Silicon	
13463-67-7	Titanium Dioxide	
7439-98-7	Molybdenum	
7631-86-9	Silicon Dioxide	

· Pennsylvania Special Hazardous Substance List:

7440-47-3	Chromium	ES
7439-96-5	Manganese	E
7440-02-0	Nickel	ES

· Carcinogenic categories:**· EPA (Environmental Protection Agency):**

7440-47-3	Chromium	D
7439-96-5	Manganese	D

· TLV (Threshold Limit Value established by ACGIH):

7789-75-5	Calcium fluoride	A4
7440-47-3	Chromium	A4
1317-95-9	Silica	A2
7440-02-0	Nickel	A5
13463-67-7	Titanium Dioxide	A4
7439-98-7	Molybdenum	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health):

1317-95-9	Silica	
7440-02-0	Nickel	
13463-67-7	Titanium Dioxide	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:**· Signal word:** Danger**· Hazard-determining components of labeling:**

Iron
Potassium Silicate
Silica
Nickel

(Contd. on page 17)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

· **Hazard statements:**

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H317 May cause an allergic skin reaction.
- H350 May cause cancer.
- H335 May cause respiratory irritation.
- H372 Causes damage to organs through prolonged or repeated exposure.

· **Precautionary statements:**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 If on skin: Wash with plenty of water.
- P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

None of the ingredients are listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other Information

SOWESCO urges each end user and recipient of this SDS to study it carefully. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product. This information is believed to be accurate as of the revision date shown above. However, no warranty, expressed or implied, is given. Because the conditions or methods of use are beyond SOWESCO's control, we assume no liability resulting from the use of this product. Regulatory requirements are subject to change and may differ between various locations. Compliance with all applicable Federal, State, Provincial, and Local laws and regulations remain the responsibility of the user.

· **Date of last revision/ revision number:** 09/26/2019 / 3

· **Abbreviations and acronyms:**

- ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 18)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/26/2019

Reviewed on 09/26/2019

Trade Name: Low-Alloy Steel Electrodes for Shielded Metal Arc Welding

VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety and Health
OSHA: Occupational Safety & Health Administration
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Sol. 2: Flammable solids – Category 2
Pyr. Sol. 1: Pyrophoric solids – Category 1
Water-react. 1: Substances and mixtures which in contact with water emit flammable gases – Category 1
Water-react. 3: Substances and mixtures which in contact with water emit flammable gases – Category 3
Ox. Sol. 1: Oxidizing solids – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 1A: Carcinogenicity – Category 1A
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106