

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

### 1 Identification

- **Product Identifier**
- **Trade Name: Filler Metals for Brazing and Braze Welding**
- **Product Number:**
  - Specification: A5.8
  - Classification: RBCuZn-C, RBCuZn-D
  - Solid wire/rod filler metals for brazing and braze welding
- **Specification: A5.8**
  - Classification: RBCuZn-C
  - Flux-coated wire/rod filler metals for brazing and braze welding
- **Relevant identified uses of the substance or mixture and uses advised against:**
  - For professional use only. Use according to manufacturer's specification.
- **Product Description:** Solid wire/rod and flux-coated wire/rod filler metals for brazing and braze welding.
- **Application of the substance / the mixture:** Industry specific application.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
  - Pinnacle Alloys I, LLC
  - 9384 Wallisville Road
  - Houston, TX 77013
  - Telephone: 800-856-9353
- **Emergency telephone number:** 713-688-9353

### 2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer. Route of exposure: Inhalation.

Toxic to Reproduction 1B

H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 1

H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.



Environment

Aquatic Acute 1

H400 Very toxic to aquatic life.



Acute Toxicity - Oral 4

H302 Harmful if swallowed.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3

H335 May cause respiratory irritation.

(Contd. on page 2)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

**Trade Name: Filler Metals for Brazing and Braze Welding**

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger
- **Hazard-determining components of labeling:**
  - Silicon
  - Nickel
  - Boric Acid salt
  - Silver
- **Hazard statements:**
  - H302 Harmful if swallowed.
  - H319 Causes serious eye irritation.
  - H317 May cause an allergic skin reaction.
  - H351 Suspected of causing cancer. Route of exposure: Inhalation.
  - H360 May damage fertility or the unborn child.
  - H335 May cause respiratory irritation.
  - H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.
  - H400 Very toxic to aquatic life.
- **Precautionary statements:**
  - P201 Obtain special instructions before use.
  - P202 Do not handle until all safety precautions have been read and understood.
  - P260 Do not breathe dust/fume/gas/mist/vapors/spray.
  - P264 Wash thoroughly after handling.
  - P270 Do not eat, drink or smoke when using this product.
  - P271 Use only outdoors or in a well-ventilated area.
  - P272 Contaminated work clothing must not be allowed out of the workplace.
  - P280 Wear protective gloves/protective clothing/eye protection/face protection.
  - P302+P352 If on skin: Wash with plenty of water.
  - P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
  - P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - P308+P313 IF exposed or concerned: Get medical advice/attention.
  - P312 Call a poison center/doctor if you feel unwell.
  - P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
  - P362+P364 Take off contaminated clothing and wash it before reuse.
  - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
  - P337+P313 If eye irritation persists: Get medical advice/attention.
  - P403+P233 Store in a well-ventilated place. Keep container tightly closed.
  - P405 Store locked up.
  - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Unknown acute toxicity:**
  - This value refers to knowledge of known, established toxicological or ecotoxicological values.
  - 51 % of the mixture consists of component(s) of unknown toxicity.
- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

(Contd. on page 3)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022


Reviewed on 09/14/2022

### Trade Name: Filler Metals for Brazing and Braze Welding

· **NFPA ratings (scale 0 - 4)**



· **HMS-ratings (scale 0 - 4)**



· **Hazard(s) not otherwise classified (HNOC):** None known

### \* 3 Composition/Information on Ingredients

· **Chemical characterization: Substance**

· **Description:** Mixture of substances listed below with non-hazardous additions.

· **Dangerous Components:**

CAS: 7440-50-8 RTECS: GL 5325000	Copper Aquatic Acute 1, H400	15-35%
CAS: 7440-22-4	Silver Specific Target Organ Toxicity - Single Exposure 3, H335; Aquatic Acute 3, H402	15-35%
CAS: 7440-21-3	Silicon Flammable Solids 2, H228; Acute Toxicity - Oral 4, H302; Eye Irritation 2B, H320; Combustible Dust	15-35%
CAS: 7440-02-0	Nickel Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 1, H372; ⚠ Sensitization - Skin 1, H317; Aquatic Acute 3, H402	13.000%
CAS: 26038-87-9	Boric Acid salt Toxic to Reproduction 1B, H360; Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Eye Irritation 2A, H319	2-12%
CAS: 1303-96-4 RTECS: ED4588000	Disodium tetraborate, decahydrate Toxic to Reproduction 1B, H360 Specific concentration limit: Toxic to Reproduction 1B; H360: C ≥ 8.5 %	2-12%
CAS: 7439-89-6 RTECS: NO 4565500	Iron Flammable Solids 2, H228; Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335; Eye Irritation 2B, H320; Combustible Dust	≤2.5%
CAS: 7439-96-5 RTECS: OO 9275000	Manganese Pyrophoric Solids 1, H250; Substances and mixtures which, in contact with water, emit flammable gases 1, H260	≤2.5%

· **Additional information:**

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

Note: Certain chemical constituents listed in Section 3 may vary depending upon the Classification of the Filler Metals for Brazing and Braze Welding products.

(Contd. on page 4)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

**Trade Name: Filler Metals for Brazing and Braze Welding**

### \* 4 First-Aid Measures

- **Description of first aid measures**

- **General information:**

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

- **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in the side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

- **After eye contact:**

Do NOT rub eyes. Immediately rinse opened eye(s) for at least 15 minutes under running water, lifting upper and lower lids occasionally. If symptoms persist, consult a physician.

If easy to do so, remove contact lenses if worn.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.

Induce vomiting and call for medical help.

If swallowed and symptoms occur, consult a doctor.

- **Information for doctor**

- **Most important symptoms and effects, both acute and delayed:**

Absorption of silver can lead to grayish blue discoloration of the skin.

- **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

### 5 Fire-Fighting Measures

- **Extinguishing media**

- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

- **For safety reasons unsuitable extinguishing agents:** No further relevant information.

- **Special hazards arising from the substance or mixture:**

Amorphous or crystalline silicon both react exothermically when heated with alkali-metal carbonates attaining incandescence and evolving carbon monoxide.

Material in powder form, capable of creating a dust explosion. Mixture of silicon, aluminum, and lead oxide explodes when heated.

If incinerated, product will release the following toxic fumes: Oxides of copper, silver, iron, manganese, nickel, silicon, zinc, boron/borates, sodium and aluminum.

- **Advice for firefighters**

- **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

- **Additional information:**

These items are not reactive, flammable, or explosive and essentially not hazardous at ambient temperatures. Welding arcs and sparks can ignite combustibles and flammable products. If involved in a fire, these products may generate irritating aluminum fumes and a variety of metal oxides. Emergency responders must wear personal protection equipment suitable for the situation. Use the extinguishing media recommended for the burning materials and fire situation. See ANSI Z49.1 "Safety in Welding and Cutting" and "Safe Practices" Code: SP, published by the American Welding Society.

(Contd. on page 5)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

**Trade Name: Filler Metals for Brazing and Braze Welding**

### \* 6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures:**

Ensure adequate ventilation.  
Avoid contact with skin, eyes and clothing.

· **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up:**

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Flammable solid. Stop leak if without risk. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources.

· **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· <b>PAC-1:</b>		
7440-50-8	Copper	3 mg/m <sup>3</sup>
7440-22-4	Silver	0.3 mg/m <sup>3</sup>
7440-21-3	Silicon	45 mg/m <sup>3</sup>
7440-02-0	Nickel	4.5 mg/m <sup>3</sup>
1303-96-4	Disodium tetraborate, decahydrate	6 mg/m <sup>3</sup>
7439-89-6	Iron	3.2 mg/m <sup>3</sup>
7439-96-5	Manganese	3 mg/m <sup>3</sup>
7784-30-7	Aluminum phosphate	14 mg/m <sup>3</sup>
· <b>PAC-2:</b>		
7440-50-8	Copper	33 mg/m <sup>3</sup>
7440-22-4	Silver	170 mg/m <sup>3</sup>
7440-21-3	Silicon	100 mg/m <sup>3</sup>
7440-02-0	Nickel	50 mg/m <sup>3</sup>
1303-96-4	Disodium tetraborate, decahydrate	190 mg/m <sup>3</sup>
7439-89-6	Iron	35 mg/m <sup>3</sup>
7439-96-5	Manganese	5 mg/m <sup>3</sup>
7784-30-7	Aluminum phosphate	200 mg/m <sup>3</sup>
· <b>PAC-3:</b>		
7440-50-8	Copper	200 mg/m <sup>3</sup>
7440-22-4	Silver	990 mg/m <sup>3</sup>
7440-21-3	Silicon	630 mg/m <sup>3</sup>
7440-02-0	Nickel	99 mg/m <sup>3</sup>
1303-96-4	Disodium tetraborate, decahydrate	1,100 mg/m <sup>3</sup>
7439-89-6	Iron	150 mg/m <sup>3</sup>
7439-96-5	Manganese	1,800 mg/m <sup>3</sup>

(Contd. on page 6)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

**Trade Name: Filler Metals for Brazing and Braze Welding**

7784-30-7	Aluminum phosphate	1,200 mg/m <sup>3</sup>
-----------	--------------------	-------------------------

### \* 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:** Open and handle receptacle with care.
- **Information about protection against explosions and fires:** Keep protective respiratory device available.
- **Conditions for safe storage, including any incompatibilities**  
Store away from strong acids, strong bases, strong oxidizing agents and strong reducing agents.
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in the original container.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

### \* 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**  
All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.
- **Components with occupational exposure limits:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

7440-50-8 Copper	
PEL	Long-term value: 1* 0.1** mg/m <sup>3</sup> as Cu *dusts and mists **fume
REL	Long-term value: 1* 0.1** mg/m <sup>3</sup> as Cu *dusts and mists **fume
TLV	Long-term value: 1* 0.2** mg/m <sup>3</sup> *dusts and mists; **fume; as Cu
7440-22-4 Silver	
PEL	Long-term value: 0.01 mg/m <sup>3</sup>
REL	Long-term value: 0.01 mg/m <sup>3</sup>
TLV	Long-term value: 0.1 mg/m <sup>3</sup> metal: dust and fume
7440-21-3 Silicon	
PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	TLV withdrawn
7440-02-0 Nickel	
PEL	Long-term value: 1 mg/m <sup>3</sup>

(Contd. on page 7)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

### Trade Name: Filler Metals for Brazing and Braze Welding

REL	Long-term value: 0.015 mg/m <sup>3</sup> as Ni; See Pocket Guide App. A
TLV	Long-term value: 1.5* mg/m <sup>3</sup> elemental, *inhalable fraction, A5, BEI
<b>1303-96-4 Disodium tetraborate, decahydrate</b>	
REL	Long-term value: 5 mg/m <sup>3</sup>
TLV	Short-term value: 6* mg/m <sup>3</sup> Long-term value: 2* mg/m <sup>3</sup> *as inhalable fraction, A4
<b>7439-96-5 Manganese</b>	
PEL	Ceiling limit value: 5 mg/m <sup>3</sup> as Mn
REL	Short-term value: 3 mg/m <sup>3</sup> Long-term value: 1 mg/m <sup>3</sup> fume, as Mn
TLV	Long-term value: 0.02* 0.1** mg/m <sup>3</sup> as Mn; A4, *respirable **inhalable fraction
· <b>Ingredients with biological limit values:</b>	
<b>7440-02-0 Nickel</b>	
BEI	5 µg/L urine post-shift at end of workweek Nickel (background)
	30 µg/L urine post-shift at end of workweek Nickel (background)

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



Suitable respiratory protective device recommended.

Use NIOSH approved or equivalent fume respirator or air supplied respirator when welding, brazing, cutting, grinding, or soldering in a confined space or general work area where local exhaust and/or ventilation does not keep exposure below the limits outlined in Section 8. Monitor the air quality inside the welder's helmet, and/or worker's breathing zone to determine if a respirator is required and the type needed.

(Contd. on page 8)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

### Trade Name: Filler Metals for Brazing and Braze Welding

· **Protection of hands:**



Protective gloves

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Helmet or face shield

Wear a helmet or face shield with a filter lens around shade number 14. Adjust if needed by selecting the next lighter or darker shade number. See ANSI/ASC Z49.1 Section 4.2 or publication F2.2. Shield other workers by providing screens and flash goggles.

· **Body protection:**



Protective work clothing

Wear approved head, hand, and body protection, which help to prevent injury from radiation, sparks, and electrical shock. This would include wearing welder's gloves and a protective face shield and may include arm protectors, apron, hats, shoulder protection, as well as dark, non-synthetic, substantial clothing. See ANSI Z49.1. Welders should be trained not to allow electrically live parts to contact the skin or wet clothing and gloves. The welders should insulate themselves from the work and ground and should not touch live electrical parts. Welders should not wear short sleeve shirts or short pants.

· **Limitation and supervision of exposure into the environment:**

Keep away from drains, surface and ground waters.  
Avoid release into the environment.

## \* 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:**

Solid Wire/Rod, or Flux-Coated Wire/Rod

**Color:**

Copper/bronze metallic color, or copper wire covered by white flux coating

· **Odor:**

Odorless until used

· **Odor threshold:**

Not determined.

· **pH-value:**

Not applicable.

· **Change in condition**

**Melting point/Melting range:**

Not determined.

(Contd. on page 9)



**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

**Trade Name: Filler Metals for Brazing and Braze Welding**

- **Flash point:** None
- **Flammability (solid, gaseous):** Not determined.
- **Ignition temperature:** Not applicable
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
  - Lower:** Not determined.
  - Upper:** Not determined.
- **Vapor pressure:** Not applicable.
- **Density:** Not determined.
- **Relative density:** Not determined.
- **Vapor density:** Not applicable.
- **Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
  - Water:** Insoluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not applicable.
  - Kinematic:** Not applicable.
- **Solvent content:**
  - VOC content:** 0.00 %
  - Solids content:** 100.0 %
- **Other information:** No further relevant information available.

**\* 10 Stability and Reactivity**

- **Reactivity:**  
Stable under normal conditions.  
May react violently or explosively on contact with water. Will react with water or steam to product hydrogen. Incompatible (violent reactions) with chlorine, fluorine, oxidizers, calcium, carbide, alkali carbonates, iodine pentafluoride, cobaltic fluoride, rubidium carbide, MnF<sub>3</sub>, nitrosyl fluoride, AgF. Mixtures of cesium acetylide with silicon react vigorously on heating. Rubidium acetylide reacts vigorously with silicon on warming.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:**  
May react violently or explosively on contact with water. Will react with water or steam to product hydrogen. Incompatible (violent reactions) with chlorine, fluorine, oxidizers, calcium, carbide, alkali carbonates, iodine pentafluoride, cobaltic fluoride, rubidium carbide, MnF<sub>3</sub>, nitrosyl fluoride, AgF. Mixtures of cesium acetylide with silicon react vigorously on heating. Rubidium acetylide reacts vigorously with silicon on warming. Contact with acids or strong bases may cause generation of gas.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:**  
Incompatible (violent reactions) with chlorine, fluorine, oxidizers, calcium, carbide, alkali carbonates, iodine pentafluoride, cobaltic fluoride, rubidium carbide, MnF<sub>3</sub>, nitrosyl fluoride, AgF.

(Contd. on page 10)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

### Trade Name: Filler Metals for Brazing and Braze Welding

Strong acids, strong bases, strong oxidizing agents and strong reducing agents.

· **Hazardous decomposition products:**

Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the processes and procedures followed, and the welding consumables used. Other conditions that also influence the composition and quantity of fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, or galvanizing), the number of welders in operation and the volume of the work area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume, and the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing procedures). When the electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 8. Fume and gas decomposition, and not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration. Also, new compounds not in the electrodes may form. The known gases and fumes that may form during welding or cutting and their exposure limits are noted in the list in Section 11 below. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 8, plus those from the base metal and coating, etc. as noted above. Chlorinated solvents may be decomposed into toxic gases such as phosgene.

It is understood, however, that the elements and/or oxides to be mentioned are virtually always present as complex oxides and not as metals (See "Characterization of Arc Welding Fume", from the American Welding Society). The elements or oxides listed Section 8 correspond to the ACGIH categories found in "Threshold Limit Values for Chemical Substances and Physical Agents" listed in Section 8. Some products will also contain: copper, silver, iron, manganese, nickel, silicon, zinc, boron/borates, sodium and aluminum. Some elements or compounds may exceed their PELs/TLVs before the total fumes exceed 5 mg/m<sup>3</sup>.

## 11 Toxicological Information

· **Information on toxicological effects:**

Effects of Over-Exposure: Electric arc welding may create one or more of the following health hazards:

- ARC RAYS can injure eyes and burn skin. Incidences of skin cancer have been reported.
- ELECTRIC SHOCK can kill.
- FUMES AND GASES GENERATED FROM WELDING can be dangerous to your health.
- PRIMARY ROUTES OF ENTRY are the respiratory system, eyes, skin, and/or indigestion.
- NOISE can damage hearing.

Short-term (acute) over-exposure effects:

- WELDING FUMES may result in discomfort, such as dizziness, nausea, or dryness or irritation of the nose, throat, or eyes.
- ALUMINUM OXIDE may cause irritation of the respiratory system.
- IRON, IRON OXIDE have no known effects. Treat as a nuisance dust or fume.
- MANGANESE, MANGANESE COMPOUNDS may cause metal fume fever, characterized by irritation of the throat, vomiting, nausea, fever, body aches, and chills. Recovery is generally complete within 48 hours of overexposure.
- NICKEL, NICKEL COMPOUNDS may cause metallic taste, nausea, tightness in chest, fever, and allergic reactions.
- COPPER may cause capillary damage, headache, cold sweat, weak pulse, and kidney and liver damage, central nervous system excitation followed by depression, jaundice, convulsions, paralysis, and coma. Death may occur from shock or renal failure.

Long-term (chronic) over-exposure effects:

- WELDING FUMES in excess levels may cause bronchial asthma, lung fibrosis, pneumoconiosis, or 'siderosis.' Overexposure to air contaminants may lead to their accumulation in the lungs, a condition which may be seen as dense areas on chest x-rays. The severity of the change is proportional to the length of exposure. The changes seen are not necessarily associated with symptoms or signs of reduced lung function or disease. In addition, the changes on X-rays may be caused by non-work

(Contd. on page 11)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

### Trade Name: Filler Metals for Brazing and Braze Welding

factors such as smoking, etc.

- ALUMINUM OXIDE may cause pulmonary fibrosis and emphysema.
- IRON, IRON OXIDE may cause siderosis or deposits of iron in the lungs, which is believed to affect pulmonary function. Lungs will clear in time when exposure to iron fumes and its compounds ceases. Iron and magnetite (Fe<sub>3</sub>O<sub>4</sub>) are not regarded as fibrogenic materials.
- MANGANESE, MANGANESE COMPOUNDS may cause central nervous system effects referred to as 'manganism.' Symptoms include languor, sleepiness, muscular weakness, emotional disturbances, spastic gait, and tremors. Behavioral changes and changes in handwriting may also appear. These effects are irreversible. Employees overexposed to manganese should receive regular medical examinations for early detection of manganism.
- NICKEL, NICKEL COMPOUNDS may lung fibrosis or pneumoconiosis. Studies of nickel refinery workers indicated a higher incidence of lung and nasal cancers.
- COPPER may cause hepatic cirrhosis, brain damage and demyelination, kidney defects, and copper deposition in the cornea as exemplified by humans with Wilson's disease. It has also been reported that copper poisoning has led to hemolytic anemia and accelerates arteriosclerosis.

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

<b>7440-22-4 Silver</b>		
Oral	LD50	>5,000 mg/kg (Rat)
	LD50 Oral	100 ml/kg (Mouse)
<b>7440-21-3 Silicon</b>		
Oral	LD50	3,160 mg/kg (Rat)
<b>26038-87-9 Boric Acid salt</b>		
Oral	LD50	1,580 mg/kg (Rat)
<b>7439-89-6 Iron</b>		
Oral	LD50	7,500 mg/kg (Rat)
<b>7439-96-5 Manganese</b>		
Oral	LD50	9,000 mg/kg (Rat)

· **Primary irritant effect:**

· **On the skin:**

Irritant to skin and mucous membranes.

May cause an allergic skin reaction.

· **On the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories:**

· **IARC (International Agency for Research on Cancer):**

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

7440-02-0	Nickel	2B
-----------	--------	----

(Contd. on page 12)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

**Trade Name: Filler Metals for Brazing and Braze Welding**

· <b>NTP (National Toxicology Program):</b>	
7440-02-0	Nickel
R	
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration):</b>	
None of the ingredients are listed.	

### 12 Ecological Information

- **Toxicity:**
- **Aquatic toxicity:**  
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

<b>7440-50-8 Copper</b>	
EC50	0.04-0.05 mg/l (Water flea)
<b>7440-02-0 Nickel</b>	
EC50	1 mg/l (Water flea)
<b>7439-96-5 Manganese</b>	
EC50	40 mg/l (Water flea)

- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Poisonous for fish and plankton in water bodies.  
Very toxic for aquatic organisms
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

### 13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household waste. Do not allow product to reach sewage system.  
Observe all federal, state and local environmental regulations when disposing of this material.
- **Uncleaned packaging**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, ADN, IMDG, IATA**                      Non-Regulated Material
- **UN proper shipping name:**
- **DOT, ADR/ADN, ADN, IMDG, IATA**                      Non-Regulated Material

(Contd. on page 13)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

**Trade Name: Filler Metals for Brazing and Braze Welding**

- **Transport hazard class(es):**
- **DOT, ADR/ADN, ADN, IMDG, IATA**
- **Class:** Non-Regulated Material
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

**15 Regulatory Information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· <b>Section 355 (extremely hazardous substances):</b>
None of the ingredients are listed.
· <b>Section 313 (Specific toxic chemical listings):</b>
7440-50-8 Copper
7440-22-4 Silver
7440-02-0 Nickel
7439-96-5 Manganese
· <b>TSCA (Toxic Substances Control Act):</b>
All components have the value ACTIVE.
· <b>Hazardous Air Pollutants</b>
7439-96-5 Manganese
· <b>California Proposition 65:</b>
 WARNING: This product can expose you to chemicals including the listed chemicals which are known to the State of California to cause cancer, birth defects and/or other reproductive harm. For more information, go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .
· <b>Chemicals known to cause cancer:</b>
7440-02-0 Nickel
· <b>Chemicals known to cause reproductive toxicity for females:</b>
None of the ingredients are listed.
· <b>Chemicals known to cause reproductive toxicity for males:</b>
None of the ingredients are listed.
· <b>Chemicals known to cause developmental toxicity:</b>
None of the ingredients are listed.
· <b>New Jersey Right-to-Know List:</b>
7440-50-8 Copper
7440-22-4 Silver
7440-21-3 Silicon
7440-02-0 Nickel
7439-96-5 Manganese



WARNING: This product can expose you to chemicals including the listed chemicals which are known to the State of California to cause cancer, birth defects and/or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

(Contd. on page 14)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

### Trade Name: Filler Metals for Brazing and Braze Welding

7784-30-7	Aluminum phosphate	
<b>· New Jersey Special Hazardous Substance List:</b>		
7440-22-4	Silver	F3
7440-21-3	Silicon	F3
7440-02-0	Nickel	CA
7439-96-5	Manganese	F3, R1
7784-30-7	Aluminum phosphate	CO
<b>· Pennsylvania Right-to-Know List:</b>		
7440-50-8	Copper	
7440-22-4	Silver	
7440-21-3	Silicon	
7440-02-0	Nickel	
1303-96-4	Disodium tetraborate, decahydrate	
7439-96-5	Manganese	
<b>· Pennsylvania Special Hazardous Substance List:</b>		
7440-50-8	Copper	E
7440-22-4	Silver	E
7440-02-0	Nickel	ES
7439-96-5	Manganese	E
<b>· Carcinogenic categories:</b>		
<b>· EPA (Environmental Protection Agency):</b>		
7440-50-8	Copper	D
7440-22-4	Silver	D
1303-96-4	Disodium tetraborate, decahydrate	I (oral)
7439-96-5	Manganese	D
<b>· TLV (Threshold Limit Value established by ACGIH):</b>		
7440-02-0	Nickel	A5
1303-96-4	Disodium tetraborate, decahydrate	A4
<b>· NIOSH-Ca (National Institute for Occupational Safety and Health):</b>		
7440-02-0	Nickel	

**· GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms:**



**· Signal word:** Danger

**· Hazard-determining components of labeling:**

Silicon  
Nickel  
Boric Acid salt  
Silver

(Contd. on page 15)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

### Trade Name: Filler Metals for Brazing and Braze Welding

· **Hazard statements:**

- H302 Harmful if swallowed.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer. Route of exposure: Inhalation.
- H360 May damage fertility or the unborn child.
- H335 May cause respiratory irritation.
- H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.
- H400 Very toxic to aquatic life.

· **Precautionary statements:**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 If on skin: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other Information

Pinnacle Alloys urges each end user and recipient of this SDS to study it carefully. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product. This information is believed to be accurate as of the revision date shown above. However, no warranty, expressed or implied, is given. Because the conditions or methods of use are beyond Pinnacle Alloys' control, we assume no liability resulting from the use of this product. Regulatory requirements are subject to change and may differ between various locations. Compliance with all applicable Federal, State, Provincial, and Local laws and regulations remain the responsibility of the user.

· **Contact:**

· **Abbreviations and acronyms:**

- ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 16)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/14/2022

Reviewed on 09/14/2022

**Trade Name: Filler Metals for Brazing and Braze Welding**

DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety and Health  
 OSHA: Occupational Safety & Health Administration  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flammable Solids 2: Flammable solids – Category 2  
 Pyrophoric Solids 1: Pyrophoric solids – Category 1  
 Substances and mixtures which, in contact with water, emit flammable gases 1: Substances and mixtures which in contact with water emit flammable gases – Category 1  
 Acute Toxicity - Oral 4: Acute toxicity – Category 4  
 Skin Irritation 2: Skin corrosion/irritation – Category 2  
 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A  
 Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B  
 Sensitization - Skin 1: Skin sensitisation – Category 1  
 Carcinogenicity 2: Carcinogenicity – Category 2  
 Toxic to Reproduction 1B: Reproductive toxicity – Category 1B  
 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3  
 Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

**\* Data compared to the previous version altered.**

SDS created by MSDS Authoring Services    www.msdsauthoring.com    +1-877-204-9106